

PrintaSleeve

Printasleeve Ltd, Higher Street, West Chinnock, Crewkerne, Somerset, TA18 7QA
Email: info@printasleeve.com Tel: 01935 881516, Fax: 01935 881314
www.printasleeve.com

PVC BS2848 Type 3 85T offers consistent quality at low cost with good dielectric strength, and resistance to moisture and ageing.

- Manufactured to a recognized British Standard
- Designed to be tough and durable
- Ideal for general purpose sleeving applications
- Can be supplied in coils and cut sleeves
- Can be plain or custom printed

Material Characteristics:

Continuous Operating Temperature:	-20°C to +85°C	
Elongation at break:	220%	ISO37
Tensile Strength:	15MPa	ISO37
Dielectric Strength:	20KV mm min	IEC 243
Insulation Resistance:	10 ¹² Ohm/cm	
Fluid Resistance:	Good	
Hardness:	BSS20-30	
Flammability:	Self-extinguishing in 30 seconds	
RoHS:	Fully Compliant	

Standard colours: Black (*other colours available upon request*)
Standard wall thickness: 0.5mm (*other sizes and thicknesses available upon request*)

Test Method



Reference	Inside Diameter (mm)	Nominal Wall (mm)	Coil Size (m)
PVC 85 10	1.0	0.5	100
PVC 85 15	1.5	0.5	100
PVC 85 20	2.0	0.5	100
PVC 85 30	3.0	0.5	100
PVC 85 40	4.0	0.5	100
PVC 85 50	5.0	0.5	100
PVC 85 60	6.0	0.5	100
PVC 85 70	7.0	0.5	100
PVC 85 80	8.0	0.5	100
PVC 85 90	9.0	0.5	100
PVC 85 100	10.0	0.5	100

Can be supplied in alternative quantities and sizes upon request.

Other grades of PVC are available. Please refer to **BS3858** and **BS2848 Type 3 105T**