

# PrintaSleeve

Printasleeve Ltd, Higher Street, West Chinnock,  
Crewkerne, Somerset, TA18 7QA

Email: [info@printasleeve.com](mailto:info@printasleeve.com) Tel: 01935 881516,  
[www.printasleeve.com](http://www.printasleeve.com)

Fax: 01935 881314

*Hot Melt Tape is a practical and easy solution where adhesion or restraint is required without, or in addition to, adhesive lined sleeving.*

- When heated, the adhesive melts and flows forming a seal
- On cooling, the adhesive in the tape hardens providing a protective and permanent seal
- Supplied in a non-tack roll form
- Can be wound in to place
- Stretching into place allows for a firmer grip

## Material Characteristics:

<b>Material:</b>	Flexible Ethylvinylacetate (EVA)
<b>Tape Width:</b>	25mm
<b>Tape Thickness:</b>	0.25mm
<b>Roll Length:</b>	50 metres
<b>Operating Temperature Range:</b>	-50°C - +105°C
<b>Melting Point:</b>	+95°C
<b>Fire Safety:</b>	Halogen-Free
<b>RoHS:</b>	Fully Compliant



## Application:

1. Clean and preheat the part or item to be protected
2. Wrap the tape around the item, stretching the tape as you do so to form a tight seal
3. Place the wrapped item in its oversleeve or casing
4. Apply moving heated airflow evenly over the surface of the sleeve or casing as usual
5. Allow to cool thoroughly

**CAUTION!** This product will remain hot for some time after the heat source is removed

**Other adhesive lined solutions are available. Please refer to our website - [www.printasleeve.com](http://www.printasleeve.com)**