

PrintaSleeve



Printasleeve Ltd, Higher Street, West Chinnock,
Crewkerne, Somerset, TA18 7QA

Email: info@printasleeve.com Tel: 01935 881516,
www.printasleeve.com

Fax: 01935 881314



PC3X is braided from slightly heavier Polyester monofilaments than our PB and PG range. It has an increased expansion ratio, allowing for greater versatility from a single size of braid.

- Ideal for covering single or multi-installation cables
- Often used for extra protection on hoses or plastic piping
- A great choice of colours giving a distinctive finish to your product
- Sleeving will fit over connectors etc. before returning to its supplied diameter
- Can be supplied in coils, reels, mini-packs or cut to length

Material Characteristics:

Filament Diameter:	0.25mm
Melting Point:	250°C
Maximum Working Temperature:	150°C
Short-Term Peak Temperature:	220°C
Minimum Working Temperature:	-50°C
Limited Oxygen Index:	34
Fume Toxicity:	passes CEI 754-1&2 (Halogen Free)
Fume Opacity:	passes NF C20452 (Polymer)
Chemical Resistance:	Unaffected by most chemicals
ROHS:	Fully Compliant



Standard Colours: Red, Orange, Yellow, Green, Royal Blue, Brown, White, Violet
Special Colours: Black and yellow hazard stripe (*Other colours available on request*)

Reference	Size (mm)	Application Range (mm)	Spool Size(m)
PC3X32	3.2	3.0 to 6.4	300
PC3X60	6.0	4.0 to 9.5	300
PC3X95	9.5	5.0 to 15.0	150
PC3X120	12.0	7.0 to 19.0	150
PC3X190	19.0	14.0 to 30.0	75
PC3X318	31.8	19.5 to 44.0	75
PC3X445	44.5	31.8 to 69.8	60
PC3X508	50.8	38.0 to 76.0	60

Can also be supplied in larger spools, coils or mini-packs, with or without dispenser boxes

Other grades of braiding are available. Please refer to **PB**, **PG**, **WAB** and **Type P**, or contact us to discuss other alternative braiding solutions