

PrintaSleeve



Printasleeve Ltd, Higher Street, West Chinnock,
Crewkerne, Somerset, TA18 7QA

Email: info@printasleeve.com Tel: 01935 881516, Fax: 01935 881314
www.printasleeve.com

SGS is a braided glass sleeving with a silicone rubber coating giving it a smooth surface

- Excellent resistance to high temperatures, gases and aggressive fluids
- Very high operating temperature
- Ecologically and physiologically harmless
- Extremely flexible
- Good resistance to moisture

Material Characteristics:

Operating Temperature Range:	-40°C to +220°C
Short-Term peak:	250°C
Dielectric Strength:	2.5KV
Flammability:	Self-extinguishing
Thermal Class:	H
RoHS:	Fully compliant
Standard Colours:	Black
Other Available colours:	Red, Yellow, Blue



Reference	Nominal i.d as supplied (mm)	Tolerance (+/-mm)	Wall Thickness (mm)	Standard reels (m)
SRG10	1.0	0.2	0.5	300
SRG20	2.0	0.2	0.5	300
SRG30	3.0	0.2	0.5	200
SRG40	4.0	0.3	0.5	200
SRG50	5.0	0.3	0.5	200
SRG60	6.0	0.3	0.6	200
SRG80	8.0	0.3	0.7	100
SRG100	10.0	0.4	0.7	100

Other sizes available on request

Can be supplied in alternative quantities on request.

Other grades of heatshrink are available. Please refer to our website - www.printasleeve.com