

PrintaSleeve



Printasleeve Ltd, Higher Street, West Chinnock,
Crewkerne, Somerset, TA18 7QA

Email: info@printasleeve.com Tel: 01935 881516,
www.printasleeve.com

Fax: 01935 881314



WAB is a flexible PET wraparound protective sleeve installed by opening up the sleeve, feeding over the installation and releasing.

- Self-closing with wraparound – side entry
- The woven construction provides flexibility, spring-back and high resistance to abrasion
- Designed to protect wiring, cables, pipes, hoses and foam insulation
- Protects from mechanical degradation due to touch conditions in vibrating installations
- Breakouts on harnesses are easy and quick to fit
- Sleeving will fit over connectors etc. before returning to its supplied diameter
- Can be supplied in coils, mini-packs or cut to length

Material Characteristics:

Specific Gravity:	1.38g/cm ³
Thickness:	0.54mm
Tensile Stress:	650N/sq mm
Elongation:	20%
Warp Yarn:	1100Dtex
Weft Yarn:	0.25 round
Flammability:	<100mm/min
Operating Temperature Range:	-50°C - +150°C
Melt Temperature:	257°C
Low Temperature Flexibility (4hrs at -55°C)	No cracking or crazing
Shrinkage (water 100°C):	2-4%
(Air 200C):	24-28%
RoHS:	Fully Compliant

Test Method

ISO R1183
BS EN 5084
FMVSS302
ASTM D2671



Standard Colours:

Black (*Other colours available –please consult us*)

Reference	Size (mm)	Application Range (mm)	Coil Size(m)
WAB05	5.0	3.0 to 9.0	50
WAB09	9.0	5.0 to 13.0	50
WAB13	13.0	8.0 to 17.0	50
WAB18	18.0	14.0 to 21.0	50
WAB25	25.0	18.0 to 25.0	25
WAB35	35.0	20.0 to 40.0	25
WAB50	50.0	30.0 to 55.0	10

Other grades of braiding are available. Please refer to *PB, PG, PC3X* and *Type P*, or contact us to discuss other alternative braiding solutions